



**Johnson
Wholesale
Floors, Inc.**

**Moisture Barriers
Self-Leveling Products
Trowelable Patch Products**

DEPENDABLE
60
YEARS
**YOUR
LEVEL BEST**

DEPENDABLE[®]
FLOOR PRODUCTS
AN ALL AMERICAN COMPANY • www.floorprep.com





Adhesive

Dependable Patch/leveling

Dependable moisture reduction barrier

Self Leveling Products



An Extended Set underlayment that remains flowable for a longer period. Offers tremendous heal and overnight cover time.



Skimflow ES



A high strength gypsum cement that delivers outstanding flexural strength and adhesion for use in many applications. Compatible with more substrates. Ideal for the thin re-surfacing of all suspended floors, gypsum, and lightweight subfloors.



GSL

Trowelable Patch Products



A "fast drying", smooth spreading, quick cover blended cement for virtually any surface.



Skimcrete XL



An ultra fine textured, latex modified cement based patch which may be used to skim or fill most substrates without priming or the use of additives. FEATHERCRETE is creamy and smooth spreading to provide a superior finish. For the installation of most any floor covering, including sheet vinyl and VCT (vinyl composition tile).



Feathercrete

Moisture Barriers



A 2-component, moisture tolerant, **zero VOCs**, epoxy based product that blocks alkalinity while retarding the moisture emission in concrete. Allows **Direct Bond** with many floor covering systems or Dependable leveling products without special primers. Works on slabs with emission rates as high as 25 lbs. MVER or 100% RH. Offered in 2 formulas (12 or 5 hour cure) to meet job requirements. A 10-year warranty is available upon application.



Vaporseal DB



A two-part product which can reduce up to 15 lbs. MVER moisture (when tested according to ASTM F1869) or 90% RH (ASTM F2170) to an acceptable level for the installation of floor covering systems **OR** to isolate cut-back and other adhesive residue to allow safe installation of floor covering without fear of discoloration or bleed through.



CUTDOWN II

 Product contains recycled material. See the LEED features section in the charts on the back page for percent of recycled material.

Dependable Coverage Guide & Product Features.

PRODUCT FEATURES	Self Leveling Products		Trowelable Patch Products	
	Skimflow ES	GSL	Feathercrete	Skimcrete XL
Bag size (lbs.)	55	40	10	25
Base Material	Blended Cement	Gypsum	Blended Cement	Blended Cement
Maximum Neat Depth	1.5 inches	3+ inches	1/2" per layer	5/8 inch
Minimum Depth	1/8 inch	1/8" or less	particle thin	0 inch
Coverage Rate per bag @ 1/8" thickness	55 sq ft.	40 sq. ft.	33 sq. ft.	11.6 sq. ft.
Working Time (minutes)	40-45	45-60	18-22	15-20
Final Set Time	3-4 Hours	1-2 Hours	38 minutes	30 Minutes
Cover Time	8-24 Hours	4-24 Hours	40 Min.	30-75 Min.
Compressive Strength	4100+	5000	2600	4000+
LEED Features				
VOC Content	0	0	0	0
Recycled Content (%)	10	0	21	10
Manufacture Site	Cleveland	Cleveland	Cleveland	Cleveland
Raw Material Origin NE Ohio (%)	35	40	-	48%

DEPENDABLE Moisture Barrier Chart

Subfloor Cover	Vaporseal DB	Cutdown II
New (7 day) concrete slabs	✓	NO
Wood	NO	✓
Cutback or other adhesive residues	NO	✓
Oil Contamination	NO	NO
PRODUCT FEATURES		
Base Material	Epoxy	Latex
Max. previous emission rate (ASTM #F 1869)	25 lbs.	15 lbs.
Surface Preparation Required Surface Contaminants Profile Required Surface Required	Remove All CSP 3-5 Open, Absorptive	Some allowed No (1) Bondable
Surface Application Condition Required	Dampen	Dry to Slightly Damp
Adhesive Compatibility	Good	Excellent
Coats Required	1	2-3
Coverage Rate - Per Unit (sq. ft. per gallon)	190-310 (80-130)	2 coats - 540 (135) 3 coats - 360 (90)
Work Time (70°- 73°F)	DB-5: 15 minutes DB-12: 30 minutes	30-40 minutes
Re-coat Time (70°- 73°F)	DB-5: 4-5 hours DB-12: 12 hours	2 to 24 hours
Cover time	DB-5: 4-5 Hours (within 5 days) DB-12: 12 hours (within 5 days)	Minimum 24-48 hours
Warranty	10-Year Full Floor	5 year full floor replacement warranty available
LEED Features		
VOC Content (g/l)	0	0
<small>(1) Floor Covering that creates tension on the surface, like glued down wood, requires the best bond for Cutdown II CSP (profile) of 2-3 is required</small>		



Johnson Wholesale Floors, Inc.

Jacksonville Location

Johnson Wholesale Floors, Inc.
8100-3 Westside Industrial Blvd.
Jacksonville, Florida 32219
904-783-0527
800-345-9318

Birmingham Location

Johnson Wholesale Floors, Inc.
200 Oxmoor Court
Birmingham, Alabama 35209
205-290-0902
800-290-0912

Orlando Location

Johnson Wholesale Floors, Inc.
4500 Seaboard Road, Suite D
Orlando, Florida 32808
407-293-8903
888-293-8903

Knoxville Location

Johnson Wholesale Floors, Inc.
3235 Middlebrook Pike
Knoxville, Tennessee 37921
865-546-1091
800-453-3797

Atlanta Location/Corporate Office

Johnson Wholesale Floors, Inc.
1874 DeFoor Avenue
PO Box 250479
Atlanta, Georgia 30325
404-352-2700
800-282-0154



Guarantee

Manufacturer guarantees its product to be free of defects and the extent of its warranty is limited to the purchase price of its product only if proved defective when used as directed. There are no other warranties or guarantees expressed or implied, and no salesman, agent, distributor or dealer has the authority to extend, alter or waive these provisions.

DEPENDABLE CHEMICAL CO., Inc. Phone: (440) 333-1123
PO Box 16307 Toll Free: (800) 227-3434
Rocky River, OH 44116-0334 Fax: (440)-333-0070
www.floorprep.com Email: dependable@floorprep.com