# Safety Data Sheet (SDS)

According to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

# Section 1: Identification of the Substance/Mixture and the Company/Undertaking

Product Name: Skimflow ES Product Code: Skim ES

Dependable, LLC. Email:

1127 Linda St. info@dependable.us

Rocky River, OH 44116 Phone:

USA 440-333-1123

Chemtrec: 1-800-424-6400

Chemtrec Global: 1-703-527-3887



Product Use: Self Leveling Underlayment

# Section 2: Hazard(s) Identification

#### **GHS Ratings:**

Oral Toxicity	Acute Tox. 4	Oral>300+<=2000mg/kg
Skin corrosive	1C	Destruction of dermal tissue: Exposure < 4 hours
		Observation < 14 days, visible necrosis in at least one animal
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after
		exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5
Skin sensitizer	1	Skin sensitizer
Carcinogen	1A	Known Human Carcinogen Based on human evidence
Reproductive toxin	1A	Based on human evidence

#### **GHS Hazards**

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H350	May cause cancer
H360	May damage fertility or the unborn child

#### **GHS Precautions**

- coaationo	
P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P260	Do not breathe dust/fume/gas/mist/vapours/spray
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P310	Immediately call a POISON CENTER or doctor/physician
P321	Specific treatment, see supplemental first aid information.

SDS for: Skim ES Page 1 of 8

P330 Rinse mouth

P363 Wash contaminated clothing before reuse

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P302+P352 IF ON SKIN: Wash with soap and water

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses if present and easy to do - continue rinsing

P308+P313 IF exposed or concerned: Get medical advice/attention
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P405 Store locked up

P501 Dispose of contents/container in accordance with

local/regional/national/international regulations. Manufacturer/supplier or the competent authority to specify whether disposal requirements apply to contents,

container or both.

#### Signal Word: Danger



# Section 3: Composition/Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Quartz	14808-60-7	30.00% - 40.00%
Limestone	1317-65-3	20.00% - 30.00%
Cement, alumina, chemicals	65997-16-2	10.00% - 20.00%
Portland cement	65997-15-1	5.00% - 10.00%
Calcium sulfate	7778-18-9	1.00% - 5.00%
Gypsum (Ca(SO4).2H2O)	13397-24-5	1.00% - 5.00%
Ethylene-vinyl acetate copolymer	24937-78-8	1.00% - 5.00%

#### Section 4: First Aid Measures

#### 4.1 Description of First Aid Measures

**After Inhalation:** Supply fresh air. If required, provide artificial respiration by qualified medical personnel. Keep patient warm. Consult doctor if symptons persist.

**After Eye Contact:** Remove contact lens if worn. Rinse opened eye for 20 to 30 minutes under running water. If symptoms persist, consult a doctor.

**After Skin Contact:** Remove all contaminated clothing. Immediately wash affected skin with lukewarm water and soap, rinse thoroughly (20 min.). If skin irritation continues, consult a doctor. **After Swallowing:** Rinse out mouth and then drink plenty of water. Do not induce vomiting. Call

for medical help immediately.

SDS for: Skim ES Page 2 of 8

Notes to Physician: Treat symptomatically

# Section 5: Firefighting Measures

Flash Point: 998 C (1,828 F)

LEL: UEL:

**5.1 Flammable Limits:** Not flammable under normal conditions. Contact with water may cause hydration, and formation of caustic alkaline material.

#### 5.2 Extinguising Media

Dry Chemical

Alcohol Resistant Foam

Carbon dioxide

Do not use water

#### 5.3 Special Hazards Arising from the Substance of Mixture

Formation of toxic gases is possible during heating or in case of fire.

#### **5.4 Hazardous Combustion Products**

Carbon oxides

Sulphur Oxides

Calcium Oxide

Aldehydes

#### 5.5 Advice for Firefighters

Wear self-contained respiratory protective device and other proper protective equipment.

#### 5.6 Fire Damage

Dispose of fire debris and contaminated fire fighting media in accordance with official regulations

#### Section 6: Accidental Release Measures

#### 6.1 Personal Precautions, Protective Equipment and Emergency Procedures

Corrosive!

Avoid dust formation

Do not breathe dust

Avoid contact with skin, eyes and clothing

Remove all non-essential people from the affected area.

Ensure adequate ventilation

Wear protective equipment

**6.2 Environmental Precautions:** Do not allow to enter sewers/ surface or ground water. Prevent seepage into sewage system, workpits and cellars.

#### 6.3 Methods and Materials for Containment and Cleaning Up:

Ensure adequate ventilation.

Pick up and arrange disposal without creating dust.

Dispose of the collected material according to regulations.

#### 6.4 Reference to Other Sections

For personal protection see Section 8

For disposal information see Section 13.

# Section 7: Handling and Storage

SDS for: Skim ES Page 3 of 8

Printed: 3/30/2016 at 12:18:53PM

#### 7.1 Precautions for Safe Handling

Corrosive!

Avoid formation of respirable particles

Do not breath vapours/dust

Do not get in eyes, on skin, or on clothing

Ensure good ventilation/exhaustions at the workplace

Make sure that all applicable workplace limits are observed.

#### 7.2 Conditions for Safe Storage, Including any Incompatibilities

Store in cool, dry conditions in well sealed receptacles

Keep receptacle tightly sealed. Store in dry conditions.

Protect from humidity and water

Storage temperature 10 - 50 °C

Do not store together with oxidizing and acidic materials.

Requirements to be Met by Storerooms and Receptacles: Observe all local and national

regulations for storage of water polluting products.

#### 7.3 Specific End Use(s)

No further relevant information available.

# Section 8: Exposure Controls/Personal Protection

#### 8.1 Control Parameters

Ingredients with limit values that require monitoring at the workplace:

Chemical Name / CAS No. OSHA Exposure Limits		ACGIH Exposure Limits	Other Exposure Limits
Quartz 14808-60-7	Not Established	0.025 mg/m3 TWA (respirable fraction)	NIOSH: 0.05 mg/m3 TWA (respirable dust)
Limestone 1317-65-3	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	Not Established	NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
Cement, alumina, chemicals 65997-16-2	PEL 15 mg/m3	Not Established	Not Established
Portland cement 65997-15-1	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	1 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
Calcium sulfate 7778-18-9	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	10 mg/m3 TWA (inhalable fraction)	NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
Gypsum (Ca(SO4).2H2O) 13397-24-5	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	10 mg/m3 TWA (inhalable fraction, listed under Calcium sulfate)	NIOSH: 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
Ethylene-vinyl acetate copolymer 24937-78-8	Not Established	Not Established	Not Established

Additional Information: The lists that were valid during the creation were used as a basis.

#### 8.2 General Protective and Hygienic Measures:

The usual precautionary measures are to be adhered to when handling chemicals. Do not eat, drink, smoke or sniff while working

SDS for: Skim ES Page 4 of 8

Keep away foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin

#### 8.3 Personal Protective Equipment:

Eye Protection: Safety glasses with side shields, goggles preferred.

Respiratory Protection: Use suitable respirator protective device in case of insufficient ventilation, required if TLV exceeded.. Use suitable respiratory protective device when dust and fumes is formed. NIOSH/MSHA respirator is advised.

Protection of Hands: Protective gloves: to avoid skin problems, the glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Reccommended glove material: Neoprene, butyl rubber gloves, note: the selection of the suitable gloves does not only depend on the material, but also on the further marks of quality and varies from manufacturer to manufacturer several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application. Protective gloves should be replaced at the first signs of wear. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Skin and Body Protection: Choose body protection according to the amount and concentration of the dangerous substance at the work place. An eyewash and safety shower stations should be available in the work area.

# Section 9: Physical and Chemical Properties

#### 9.1 Information on Basic Physical and Chemical Properties

Appearance: Solid - Grey Powder Odor: None

Odor threshold: N/A Vapor Pressure: N/A

Vapor Density: N/A **pH**: 10-12

Specific Gravity: 2.6-3.0 Freezing point: N/A

Solubility: <55 g/L Boiling range: N/A

Flash point: N/A Flammability: Not Flammable

Partition coefficient (n- N/A **Autoignition** N/A octanol/water): temperature:

**Decomposition** Not Available Viscosity: Not Availabe

temperature:

# Section 10: Stability and Reactivity

Grams VOC less water: N/A

#### 10.1 Reactivity:

Stable under recommeded storage conditions. Interaction with water may cause hydration and formation of alkaline material. No decomposition if stored and applied as directed.

#### 10.2 Chemical Stability:

No decomposition if stored and applied as directed.

#### 10.3 Possibility of Hazardous Reactions:

SDS for: Skim ES Page 5 of 8 Printed: 3/30/2016 at 12:18:53PM

Hazardous polymerization will not occur.

# Section 11: Toxicological Information

**Mixture Toxicity** 

Oral Toxicity LD50: 1,358mg/kg

11.1 Information on Toxicological Effects

Routes of Entry: Target Organs:

**Effects of Overexposure** 

**Carcinogenicity:** The following chemicals comprise 0.1% or more of this mixture and are listed and/or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA (mandatory listing), or ACGIH (optional listing).

<u>CAS Number</u> <u>Description</u> <u>% Weight</u> <u>Carcinogen Rating</u>

14808-60-7 Quartz 30 to Quartz: NIOSH: potential 40% occupational carcinogen

IARC: Human carcinogen

OSHA: listed

# Section 12: Ecological Information

#### 12.1 Persistence and Degradability

**Product:** No further relevant information available

#### 12.2 Bioaccumulative Potential

Product: No further relevant information available

#### 12.3 Mobility in Soil

<u>Product:</u> Distribution among environmental compartments: No further relevant information available.

#### **Additional Ecological Information:**

German Hazard Water Class NWG

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### 12.4 Results of PBT and vPvB Assessment:

Assessment: This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

#### 12.5 Other Adverse Effects

**Product:** No further relevant information available

#### 12.6 Toxicity

#### **Component Ecotoxicity**

Calcium sulfate 96 Hr LC50 Lepomis macrochirus: 2980 mg/L [static]; 96 Hr LC50 Pimephales

promelas: >1970 mg/L [static]

# Section 13: Ecological Information

#### 13.1 Waste Treatment Methods

SDS for: Skim ES Page 6 of 8

**<u>Product:</u>** The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches the chemical or used container. Offer surplus and nonrecyclable solutions to a licensed disposal company. Send to a licensed waste management company.

Contaminated Packaging: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers

# Section 14: Transport Information

#### 14.1 UN Number:

None - Not Regulated

### Section 15: Regulatory Information

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prop 65 - Chemicals Known to Cause Developmental Toxicity

- None

Prop 65 - Chemicals Known to Cause Cancer:

14808-60-7 Quartz

- U.S. CERCLA/SARA Hazardous Substances and their Reportable Quantities
  - None
- U.S. CERCLA/SARA Section 302 Extremely Hazardous Substances EPCRA RQs
  - None
- U.S. CERCLA/SARA Section 302 Extremely Hazardous Substances TPQs
  - None
- U.S. CERCLA/SARA Section 313 Emission Reporting
  - None
  - None

TSCA (Toxic Substances Control Act)

- None

Country **Regulation** USA

Inventory - United States - Section 8(b) Inventory (TSCA)

DSL (Canadian Domestic Substance List)

**EU Risk Phrases** 

Canada

Safety Phrase

SDS for: Skim ES Page 7 of 8

Printed: 3/30/2016 at 12:18:53PM

**All Components Listed** 

Yes

Yes

#### Section 16: Other Information


#### **Hazardous Material Information System (HMIS)**

# FLAMMABILITY 0 PHYSICAL HAZARD 0 PERSONAL PROTECTION E

HMIS & NFPA Hazard Rating Legend

- \* = Chronic Health Hazard
- 0 = INSIGNIFICANT
- 1 = SLIGHT
- 2 = MODERATE
- 3 = HIGH

#### **National Fire Protection Association (NFPA)**



We believe the information contained in this SDS is correct, however, because the material may be used under conditions over which we have no control, we give no warranty and assume no responsibility for any damage to person, property or business arising from such use. It is the responsibility of the user to ensure it is properly used. Recipients are advised to confirm in advance of need that the information is current, applicable and suitable to their circumstances. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Reviewer Revision

Date Prepared: 3/30/2016