

# SAFETY DATA SHEET

## Section 1 - Product and Company Identification

**Product Name: Consolcrete Part B    Product Code: Consolcrete Part B**

Dependable LLC.  
1127 Linda St.  
Rocky River, OH 44116

Email:  
info@dependable.us  
Phone:  
440-333-1123



Mailing Address:  
P.O. Box 241354  
Mayfield Heights, OH 44124

**Chemtrec: 1- 800-424-6400**  
**Chemtrec Global: 1-703-527-3887**

Product Use: Industrial Use Only

## Section 2 - Hazards Identification

### GHS Ratings:

Oral Toxicity	Acute Tox. 3	Oral>50+<=300mg/kg
Skin corrosive	1B	Destruction of dermal tissue: Exposure < 1 hour Observation < 14 days, visible necrosis in at least one animal
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5
Skin sensitizer	1	Skin sensitizer
Mutagen	1B	Known to produce heritable mutations in human germ cellsSubcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
Carcinogen	1B	Presumed Human Carcinogen, Based on demonstrated animal carcinogenicity
Reproductive toxin	1B	Presumed, Based on experimental animals

### GHS Hazards

H301	Toxic if swallowed
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H340	May cause genetic defects
H350	May cause cancer
H360	May damage fertility or the unborn child

### GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P260	Do not breathe dust/fume/gas/mist/vapours/spray
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection

P281	Use personal protective equipment as required
P310	Immediately call a POISON CENTER or doctor/physician
P321	Specific treatment, see supplemental first aid information.
P330	Rinse mouth
P363	Wash contaminated clothing before reuse
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P302+P352	IF ON SKIN: Wash with soap and water
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P405	Store locked up
P501	Dispose of contents/container in accordance with local/regional/national/international regulations. Manufacturer/supplier or the competent authority to specify whether disposal requirements apply to contents, container or both.

**Signal Word: Danger**



Unnecessary exposure to any chemical should be avoided. NOTICE--Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after applicable limits. Follow respirator manufacturer's directions for respirator use.

### Section 3 - Composition Information On Ingredients

Chemical Name	CAS number	Weight Concentration %
Phenol, 4-nonyl-, branched	84852-15-3	50.00% - 60.00%
Propylene glycol diamine, 2-amino-, diether with Propylene	9046-10-0	20.00% - 30.00%
2,4,6-Tri(dimethylaminomethyl)phenol	90-72-2	5.00% - 10.00%
4-tert-Butylphenol	98-54-4	1.00% - 5.00%
1,3-Benzenedimethanamine	1477-55-0	1.00% - 5.00%
Trimethylhexamethylenediamine	25620-58-0	1.00% - 5.00%
Phenol, 2-nonyl-, branched	91672-41-2	1.00% - 5.00%
Naphtha, petroleum, heavy alkylate	64741-65-7	0.10% - 1.00%

### Section 4 - First Aid

**After inhalation:**

If inhaled, move person into fresh air. Monitor respiratory function. If required, provide artificial respiration. Keep

patient warm. Seek immediate medical advice. Show this sheet to doctor.  
In case of unconsciousness place patient stably in position for transportation.

**Eye Contact:**

Eye contact may cause severe irritation, redness, tearing and blurred vision. Eye contact can cause moderate irritation, redness and tearing. Eye contact may cause temporary discomfort and burns.

**After eye contact:**

Rinse opened eye for at least 15 minutes under running water. Remove contact lenses if present and easy to do so. If symptoms persist, consult a doctor.

**Skin Contact:**

Remove contaminated clothing. Wash affected skin with lukewarm water and soap for at least 20 min. Can be absorbed through the skin. Skin contact can cause reddening, irritation, dermatitis, possible sensitization. If skin irritation continues, consult a doctor.

**Ingestion:**

Ingestion can cause gastrointestinal irritation, nausea, vomiting, diarrhea and burns.

**After Ingestion:**

Drink copious amounts of water and provide fresh air. Immediately call a doctor. DO NOT induce vomiting unless instructed to do so. Material can enter lungs (aspiration hazard) during swallowing or vomiting resulting in lung inflammation or lung injury. Never give anything by mouth to an unconscious person.

**Warning:**

This product may aggravate existing skin disease. Inhalation of product may aggravate existing chronic respiratory problems. Seek medical attention immediately if difficulty breathing persists or blue color to the skin (cyanotic) after exposure.

<b>Section 5 - Fire Fighting Measures</b>
---

Flash Point: 127 C (261 F)

LEL:

UEL:

**Suitable extinguishing agents:**

CO2, sand, extinguishing powder. Do not use water for solvent based products.  
Fight larger fire with alcohol resistant foam.

**For safety reasons unsuitable extinguishing agents:**

Do not use volume water jet.

**Fire Hazards**

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Vapors may be heavier than air and may travel along the ground before ignition/flashing back to vapor source. Keep welding or cutting equipment away from product.

Dispose of fire debris and contaminated firefighting material in accordance with official regulations .

**Hazardous Combustion Products**

Carbon oxides, nitrogen oxides, low molecular weight hydrocarbons/amines

**Fire Fighting Notes**

Clear fire area of unprotected personnel. Containers that are exposed to intense heat should be cooled with water.

Avoid spreading burning liquid with the water used for cooling purposes . Do not enter fire area without protective gear. Fight fire from safe distance or a protected location.

## Section 6 - Accidental Release Measures

### **Personal precautions, protective equipment and emergency procedures:**

Corrosive!

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Wear protective clothing.

Avoid strong oxidizing agents.

Keep from contacting skin or eyes.

Avoid breathing vapors, mist, or gas.

Ensure adequate ventilation.

Evacuate personnel to safe areas.

If any equipment is necessary, ensure that it is non-sparking and electrically-protected .

### **Environmental precautions:**

Do not allow product to reach sewage system or any water source.

In case of seepage into the ground inform responsible authorities

Prevent from spreading (e.g. by damming-in or oil barriers).

Keep contaminated washing water and dispose of appropriately

### **Methods and material for containment and cleaning up:**

Ensure adequate ventilation

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste.

Do not flush with water or aqueous cleansing agents.

Send for recovery or disposal in suitable receptacles according to local, state and federal regulations

## Section 7 - Handling and Storage

### **Precautions for safe handling:**

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Avoid contact with eyes.

Ensure good ventilation/exhaustion at the workplace.

Open and handle container with care.

Prevent formation of aerosols.

Avoid breathing vapors or mist.

### **Handling:**

Apply proper ventilation, possibly combined with local exhaust. Do not eat, smoke or drink during use.

For personal protection see Section 8.

Keep away from sources of ignition.

Keep material out of reach of children.

Use only explosion proof equipment.

Wash thoroughly after handling.

### **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges by bonding and grounding product containers before and during material

transfers.

Keep respiratory protective device available.

**Conditions for safe storage, including any incompatibilities:**

**Storage:**

Keep away from sources of ignition - no smoking. Store in a cool, well ventilated place. Keep in original, closed packaging. Comply with governmental regulations.

Keep container tightly closed

Do not store in direct sunlight

**Specific end use(s):**

**FOR INDUSTRIAL USE ONLY!**

**Section 8 - Exposure and Personal Protection**

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Phenol, 4-nonyl-, branched 84852-15-3	Not Established	Not Established	Not Established
Propylene glycol diamine, 2-amino-, diether with Propylene 9046-10-0	Not Established	3 mg/m3 (respirable fraction)	Not Established
2,4,6-Tri (dimethylaminomethyl) phenol 90-72-2	Not Established	Dermal rat: 125 mg/kg	Not Established
4-tert-Butylphenol 98-54-4	Not Established	Not Established	Not Established
1,3-Benzenedimethanamine 1477-55-0	Not Established	0.1 mg/m3 Ceiling	NIOSH: 0.1 mg/m3 Ceiling
Trimethylhexamethylenedia mine 25620-58-0	Not Established	Not Established	Not Established
Phenol, 2-nonyl-, branched 91672-41-2	Not Established	Not Established	Not Established
Naphtha, petroleum, heavy alkylate 64741-65-7	TLV: 300ppm	TWA: 300ppm	Not Established

**General Hygiene Considerations:**

Avoid contact with eyes, skin and clothing. Do not breathe vapors/dust. Do not eat drink or smoke when using this product. Clean all contaminated equipment after use and isolate contaminated clothing.

**Ventilation:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

**Respiratory Protection:**

In outdoor or open areas use (NIOSH/MSHA approved) mechanical filter respirator to remove solid airborne particles of overspray during spray application. In restricted ventilation areas use (NIOSH/MSHA approved) chemical-mechanical

filters designed to remove a combination of particulate and gas and vapor. In confined areas use (NIOSH/MSHA approved) airline type respirators or hoods. Respiratory protection may also be necessary in any later manufacturing operations in which the product may become airborne in the form of vapor or dust.

**Protective Gloves:**

Protective gloves are required for prolonged or repeated contact. Wear resistant gloves such as natural rubber, neoprene, buna N or nitrile. An apron should be worn to avoid skin contact. (Consult your safety equipment supplier.)

**Eye Protection:**

Avoid contact with eyes. Wear goggles if there is a likelihood of contact with eyes. (Consult your safety equipment supplier.) Eyewash stations and safety showers should be readily available in use and handling areas. Contact lenses pose a special hazard; soft lenses may absorb irritants and all lenses concentrate them.

**Body Protection:**

Chemically resistance gloves, apron and safety goggles are recommended. Type of protective equipment should be selected based on concentration amount and conditions of use of this material.

**Contaminated Gear:**

Dispose of in accordance with official regulations.

**Section 9 - Physical and Chemical Properties**

<b>Appearance</b> Liquid	<b>Physical State</b> Liquid
<b>Vapor Density</b> Not Determined	<b>VOC</b> 9.7 %
<b>Evaporation Rate</b> Not determined	<b>Boiling Range</b> 232 to 247 °C, 450 to 477 °F
<b>Specific Gravity (SG)</b> 0.974	<b>Coating VOC (EPA calculation) lb/gl</b> 0.00
<b>Coating VOC (as supplied) lb/gl</b> 0.00	<b>WPG</b> 8.01 lbs./gal

**Section 10 - Stability and Reactivity**

**Product Stability:**

Stable under recommended storage and handling procedures.

UNSTABLE

**Incompatibilities:**

Avoid contact with strong oxidizing agents.

This product reacts with water.

**Hazardous Decomposition:**

Thermal decomposition may form toxic materials; carbon dioxide, carbon monoxide, etc. Thermal decomposition may form toxic materials; carbon dioxide, carbon monoxide, various hydrocarbons, etc.

Hazardous polymerization will not occur.

**Section 11 - Toxicological Information**

**Mixture Toxicity**

Oral Toxicity LD50: 63mg/kg  
Dermal Toxicity LD50: 2,869mg/kg

#### Component Toxicity

84852-15-3	Phenol, 4-nonyl-, branched Oral LD50: 1,300 mg/kg (Rat) Dermal LD50: 2,031 mg/kg (Rabbit)
90-72-2	2,4,6-Tri(dimethylaminomethyl)phenol Oral LD50: 1,200 mg/kg (Rat) Dermal LD50: 1,280 mg/kg (Rat)
98-54-4	4-tert-Butylphenol Oral LD50: 3,250 µL/kg (Rat) Dermal LD50: 2,318 mg/kg (Rabbit)
1477-55-0	1,3-Benzenedimethanamine Oral LD50: 660 mg/kg (Rat) Dermal LD50: 2 g/kg (Rabbit) Inhalation LC50: 700 ppm (Rat)

**Eyes      Kidneys      Liver      Skin      Respiratory System**

#### Effects of Overexposure

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
64741-65-7	Naphtha, petroleum, heavy alkylate	0.1 to 1.0%	Naphtha, petroleum, heavy alkylate: EU REACH: Present (P)

## Section 12 - Ecological Information

#### Environmental Impact Statement/Toxicity:

**Aquatic toxicity:** No further relevant information available

**Persistence and degradability:** No further relevant information available

**Bioaccumulative potential:** No further relevant information available.

**Mobility in soil:** No further relevant information available.

**Other adverse effect:** No further relevant information available

#### Component Ecotoxicity

Phenol, 4-nonyl-, branched	96 Hr LC50 Pimephales promelas: 0.135 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 0.1351 mg/L [flow-through] 48 Hr EC50 Daphnia magna: 0.14 mg/L 96 Hr EC50 Pseudokirchneriella subcapitata: 0.36 - 0.48 mg/L [static]; 72 Hr EC50 Pseudokirchneriella subcapitata: 0.16 - 0.72 mg/L [static]; 72 Hr EC50 Desmodesmus subspicatus: 1.3 mg/L
4-tert-Butylphenol	96 Hr LC50 Pimephales promelas: 4.71 - 5.62 mg/L [flow-through]; 96 Hr LC50 Cyprinus carpio: 6.9 mg/L [static] 48 Hr EC50 Daphnia magna: 3.9 mg/L; 48 Hr EC50 Daphnia magna: 3.4 - 4.5 mg/L [Static] 72 Hr EC50 Desmodesmus subspicatus: 11.2 mg/L
Trimethylhexamethylenediamine	72 Hr EC50 Desmodesmus subspicatus: 29.5 mg/L
Naphtha, petroleum, heavy alkylate	48 Hr LC50 Mysidopsis bahia: 2 mg/L 72 Hr EC50 Pseudokirchneriella subcapitata: 30000 mg/L

## Section 13 - Disposal Considerations

#### Waste treatment methods:

**Recommendation:**

Must not be disposed of together with household garbage.  
Do not allow product to reach sewage system.

Disposal of this product and any by-products must at all times comply with local, state and Federal regulations for hazardous wastes. All entities that store, transport or handle hazardous waste must take the necessary measures to prevent risks of pollution, release into the environment or damage to people and animals.

**Contaminated Packaging:**

Waste packaging should be recycled. Care should be taken when handling emptied containers that have not been cleaned. Empty containers retain some product residues. Vapor from that residue may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers.

<b>Section 14 - Transportation Information</b>
--

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
ADR	Alkylphenols, liquid, N.O.S. (contains Nonylphenol)	UN3145	III	8
DOT	Alkylphenols, liquid, N.O.S. (contains Nonylphenol)	UN3145	III	8
EMS	Number: F-A, S-B			
IATA	Alkylphenols, liquid, N.O.S. (contains Nonylphenol)	UN3145	III	8
IMDG	Alkylphenols, liquid, N.O.S. (contains Nonylphenol)	UN3145	III	8
TDG	Alkylphenols, liquid, N.O.S. (contains Nonylphenol)	UN3145	III	8

<b>Section 15 - Regulatory Information</b>
--

**Regulatory Information:**

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
USA	Inventory - United States - Section 8(b) Inventory (TSCA)	Yes

**EU Risk Phrases****Safety Phrase**

U.S. - TSCA:  
- None  
U.S. - SARA:

<b>Section 16 - Regulatory Information</b>
--



**\*DISCLAIMER\***

**THE INFORMATION CONTAINED HEREIN WAS RECEIVED FROM OUR RAW MATERIAL SUPPLIERS AND OTHER SOURCES. CANSTO PAINT COMPANY MAKES NO EXPRESS OR IMPLIED WARRANTIES REGARDING THE ACCURACY OF THE ABOVE INFORMATION AND YOU SHOULD NOT RELY ON IT. YOU SHOULD TEST THIS PRODUCT FOR CHEMICAL COMPOSITION AND CONSULT APPLICABLE SAFETY AND MEDICAL STANDARDS AND PROFESSIONAL RELATED THERETO. CANSTO PAINT COMPANY DOES NOT WARRANT THE SUITABILITY OF THE PRODUCT FOR ANY APPLICATION BY THE USER, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.**

Reviewer Revision

Date Prepared: 2/8/2017