

# WATERPROOFING TAPE KEEDEBAND™



## DIVISION

Division 9  
Tile Finishes 09 30 95  
Acoustical Treatments 09  
800

## PACKAGING

KeedeBand™  
• 50' LF  
• 5" Wide

## APPROVED SUBSTRATES

Around the perimeter of a room where KeedeRoll™ 300 is installed.

FloorPrep's KeedeBand™ is a triple layer waterproofing band designed for the KeedeRoll™ 300 uncoupling mat. It is designed for use under the seams and the perimeter of the wall where KeedeRoll™ 300 is used. KeedeBand™ completes the waterproofing system of the Dependable KeedeRoll 300™.

## Properties

A 5" wide roll on a 3" core consisting of 50 Linear Feet.

## Features

- Waterproof fabric
- Double laminated
- 5" width for easy installation

## Material and Storage Requirements

1. Deliver and keep materials in original packaging until ready to use.
2. All claims of damage must be reported to the freight company. Report any defects in material to Dependable immediately.

## Floor Requirements

### WOOD

OSB and plywood are approved substrates for KeedeRoll™ 300 and KeedeBand™. Ensure the flooring is structurally sound and built to code, with movement joists placed in accordance with industry standards.

### Substrate Preparation

- Ensure the subfloor is properly fastened, structurally sound and built to code.
- Clear any dust, paint, oil, wax or potential bond breaker from the floor. Consult Technical Services if you have any questions.
- The subfloor MUST be flat and level. If leveling is required use a Dependable self-leveler or patching product such as Skimflow® ES or Skimcrete® XL. Consult the product's data sheet for details.

### Approved Thin-sets and Grouts

- Any modified thin-set in accordance with ANSI A118.14 or ANSI A118.11.
- Any unmodified thin-set in accordance with ANSI A118.1.

### CONCRETE

Concrete is an approved substrate for KeedeRoll™, ensure it is structurally sound prior to installation.

### KeedeBand™ Installation

Follow these steps for waterproofing only

- Apply thin-set at the wall joints.
- Place KeedeRoll™ 300 5" waterproofing band (KeedeBand™) in the center between the wall and floor.
- Trace additional thin-set over the tape using the flat side of the trowel ensuring 100% bond and no excess mortar or air pockets.
- Install KeedeRoll™ 300 per instructions on KeedeRoll™ 300 technical data sheet.
- Place additional tape below where one roll ends and a new roll begins, and where no selvage edge is provided. Secure with mortar on top and bottom. Cover with KeedeRoll™. Consult technical services prior to using StepSoft™ with any floor heating systems to ensure the product is suitable for this application.

LIMITED WARRANTY:  
Dependable, LLC warrants to the initial purchaser only that the goods sold hereunder will be free from defects in material and workmanship and, except as otherwise set forth herein, will conform to the specifications provided. If any failure to meet this warranty appears within one year from the date of shipment of the goods, on the condition that Dependable, LLC. will correct any such failure by either replacing or repairing any defective goods, at Dependable, LLC's option.

The preceding paragraph sets forth the exclusive remedy for all claims based on failure of or defect in the goods sold hereunder, whether such failure or defect arises before or during the warranty period and whether a claim, however instituted, is based on contract, indemnity, warranty, tort (including negligence), strict liability or otherwise. The forgoing warranty is exclusive and is in lieu of all other warranties whether written, oral, implied or statutory.

**24 HOUR EMERGENCY:  
CHEMTREC®  
1-800-424-9300  
NON-TOXIC and  
NON-FLAMMABLE**

Keep container closed and keep away from children. May cause slight eye abrasion or irritation if spilled or rubbed in eyes. Flush thoroughly with water.

If taken internally, call a physician. Technical Assistance:  
Visit our website: [floorprep.com](http://floorprep.com) or call 1-800-227-3434.



Flooring Experts since 1951



*Published technical data & instructions are subject to change without notice. Please contact Dependable for the most current technical data, safety data & application instructions.*

© 2018 Dependable, LLC™, all rights reserved. Printed in U.S.A. All logos/images are trademarks of Dependable, LLC. Cleveland, OH USA.

**800 | 227 | 3434**  
**info@dependable.us P 440 | 333 | 1123**  
**floorprep.com F 440 | 333 | 3781**

2020/7  
2/2