

UNIVERSAL STUCCO BASE COAT

PACKAGING

50 lb. bag

YIELD

.45 Cubic Ft. per Bag

STORAGE

Store in cool and dry conditions, out of direct sunlight in sealed containers. **DO NOT ALLOW TO FREEZE.** If material freezes, dispose in accordance with local, state and federal regulations.

LIMITED WARRANTY

Universal Stucco Base Coat is warranted by Dependable, LLC to the initial purchaser only that the goods sold hereunder will be free from defects in material and workmanship and, except as otherwise set forth herein, will conform to the specifications provided. If any failure to meet this warranty appears within one year from the date of shipment of the goods, on the condition that Dependable, LLC. will correct any such failure by either replacing or repairing any defective goods, at Dependable, LLC's option.

The preceding paragraph sets forth the exclusive remedy for all claims based on failure of or defect in the goods sold hereunder, whether such failure or defect arises before or during the warranty period and whether a claim, however instituted, is based on contract, indemnity, warranty, tort (including negligence), strict liability or otherwise. The forgoing warranty is exclusive and is in lieu of all other warranties whether written, oral, implied or statutory.

Elastiment Universal Base Coat is a contractor grade pre-blended scratch and base coat used for stucco systems. Universal Base Coat may be troweled or spray applied, and is available in grey or white. Universal Base Coat is ASTM C926 compliant.

PREPARATION AND APPLICATION

FOR PROFESSIONAL USE ONLY

Install your wire mesh or lath prior to applying the Universal Base Coat and must be in accordance with ASTM C926 or local building codes. ASTM C926 also specifies the placement of control joints.

Mix Universal Base Coat with 3.25-3.5 quarts of water per bag using a hand mixed or machine paddle type mixer for 3-5 minutes. If more water is required to achieve a workable consistency, slowly add small amounts of water to the mix to achieve the desired consistency. Do not mix more material than you can apply in an hour.

Universal Base Coat is intended only for applications over code approved metal lath, per the standards of ASTM C926. Apply the Universal Base Coat in accordance to ASTM C926 and local building codes, you may use a trowel or a sprayer following standard stucco installation techniques.

Provide sufficient moisture to ensure the curing of the Universal Base Coat. Local climate and jobsite conditions will determine the curing of the product.

elastiment



800 | 227 | 3434
info@dependable.us P 440 | 333 | 1123
floorprep.com F 440 | 333 | 3781